DUVON™

FORGE X

100W / 150W / 200W

Product Overview

Next-generation LED high bay lighting system engineered for superior efficiency, refined optical control, and extended operational reliability. Designed for facilities seeking higher performance and reduced total cost of ownership.

Applications

Sports & Recreation

- Indoor courts (basketball, pickleball, etc.)
- Training gyms & fitness facilities
- Multi-purpose recreation centers
- School gymnasiums

Industrial & Infrastructure

- Warehouse & distribution centers
- Manufacturing & assembly floors
- Maintenance garages & service bays
- Cold storage & large refrigerated rooms

Performance Highlights

- **Next-generation** high-efficacy LED platform
- **Enhanced optical control** for improved uniformity and reduced glare
- **Advanced thermal management** supporting extended service life
- **Flicker-free performance** for indoor sports and video recording
- **Optimized for medium- to high-mounting** height installations
- **5-year limited manufacturer's warranty**

Engineered, Manufactured & Supported in-House

Duvon™ designs and manufactures complete LED lighting systems and turnkey solutions engineered for predictable performance, long-term reliability, and simplified service. Our systems deliver precision and uniformity across sports, stadium, industrial, and municipal applications.

5 YEAR WARRANTY

Specifications

Performance & Environmental Ratings	
Available Beam Angles	60° / 90° / 120°
Operating Temp	-40°F to 122°F
Protection Rating	IP20 / IP65 (opt.)
Rated Life	L70 ≥ 50,000 hrs
Warranty	5 years

Lumen Output	
APL-AIOHBL (100W)	15,000 lm
APL-AIOHBL (150W)	22,500 lm
APL-AIOHBL (200W)	30,000 lm

Construction & Mounting	
Housing Material	Die-cast aluminum
Finish	Outdoor rated powder coating
Color	Black / White / Custom
Weight	6.613 lbs
Mounting	Hook mount / U-Bracket (opt.)
Cover	Options available

Electrical & Control Components	
LED Chips	Philips / Osram
Drivers	Lifud
Surge Protection	10kV / 20kV (opt.)
Controls	Smart control available (opt.)

Specifications references the standard model; variant data may vary.
Motion sensor option available by customization.
Example IES files available.

Luminous Intensity Distribution





Electrical Data — Input Current (Amps)

(Nominal value shown; actual values may vary by driver configuration...)

Input Voltage	100W	150W	200W
110V	0.91A	1.36A	1.82A
240V	0.42A	0.63A	0.83A
277V	0.36A	0.54A	0.72A
480V	0.21A	0.31A	0.42A

Ordering Information

Select one option from each column to build the model number. Contact Duvon™ for custom options.

Ex: 12 — DV-AIOHBL100N — 100 — 5K — 70 — 25 — 100-277V — ACCHBL001 — ACCHBL005 — SC

Qty.	Model No.	Watts	Color	CCT	CRI	Optic	Input Power	Accessories	Smart Ctrl (opt.)
	DV-AIOHBL100N	100	Black	3K = 3000K	70	90°	100-277V	ACCHBL(001-5)	SC = Included
	DV-AIOHBL150N	150	White	4K = 4000K	80	120°	277-480V		[Blank] = None
	DV-AIOHBL200N	200		5K = 5000K	90				

Standard stock: 5000K CCT | 70 CRI (3000K - 6500K CCT / Other CRI options available).

All technical specifications and datas are subject to modification at any time and without notice.
Contact us for the most up-to-date information or visit www.duvonlighting.com
710 Armstrong Dr, Buffalo Grove, IL 60089 / Phone: (224) 567-8070 / Email: sales@duvonlighting.com

Dimensions





Accessories

Add accessory part numbers in the ordering information.

ACCHBL001

ACCHBL002

ACCHBL003

ACCHBL004

ACCHBL005

All technical specifications and datas are subject to modification at any time and without notice.
Contact us for the most up-to-date information or visit www.duvonlighting.com
710 Armstrong Dr, Buffalo Grove, IL 60089 / Phone: (224) 567-8070 / Email: sales@duvonlighting.com

① Wireless Zigbee Controller

Versatile Control: Features on/off, dimming, scheduling, and optional clouDV-based monitoring.
Pre-Programmed Switch: Five-button switch with preset dimming for easy operation.
Flexible Connectivity: Compatible with LAN, Wi-Fi, or cellular networks.
Durable Design: Weather-resistant for reliable outdoor use.
Scene Management: Supports Static, Dynamic, and ProFX lighting scenes.

② Wireless DMX Controller

Advanced Control: Includes on/off, dimming, scheduling, scene management, and clouDV-based monitoring.
Mobile App: Easy scene activation and control via Android/iOS devices.
Integrated Display: Real-time system monitoring and configuration updates.
Dynamic RGB: Supports vibrant RGB lighting and customizable scenes.
Reliable Connectivity: Offers cellular and LAN options with interference-free Sub-GHz RF.
Weather-Resistant: Built for harsh outdoor conditions.
Effortless Setup: Simplified commissioning for quick installation.
24/7 Monitoring: Cellular connectivity ensures real-time updates and optimization.

All technical specifications and datas are subject to modification at any time and without notice.
Contact us for the most up-to-date information or visit www.duvonlighting.com
710 Armstrong Dr, Buffalo Grove, IL 60089 / Phone: (224) 567-8070 / Email: sales@duvonlighting.com